



# IMPAK FILMS US LLC

## White and Metallized White PET Films

Product	Description	Gauge	Yield in <sup>2</sup> /lb	Barrier		Key P Optical
				WVTR	OTR	
<b>WHITE PET</b>						
IMP252	One Side Treated White Heat Sealable PET	80	24,200	---	---	Gloss 45°: 35%
IMP284	Two Side Treated White PET	48	41,850	---	---	Haze: 98% Opacity: 70%
IMP286	One Side Treated White PET	48	41,850	---	---	Haze: 98% Opacity: 70%
<b>METALLIZED WHITE PET</b>						
IMP254	Two Side Treated Metallized PET	80	24,200	0.30	0.35	O.D: > 2.2
IMP280	Metallized White PET	48	41,850	0.05	0.05	O.D: > 2.5
IMP281	Metallized White PET	48	40,500	0.05	0.06	O.D: > 2.5 MET Bond Strength: >600 g/in



Properties

Other

SIT: 240°F

Seal: >500 g/in

COF:

Static: ≤ 0.45

Dynamic: ≤ 0.40

COF:

Static: ≤ 0.45

Dynamic: ≤ 0.50

COF: Dynamic:

0.40 - 0.60

COF:

Static: ≤ 0.60

Dynamic: ≤ 0.55